SUPERSPEED CERTIFIED USB

LC-POWER

> 85% EFFICIENCY ErP 2014 COMPLIANT

ATX 649B

(incl. LC420-12 V2.31)

Case type:	Midi-Tower	Audio port:	HD Audio
Motherboard:	ATX, Micro-ATX, Mini-ITX	USB 3.0 port:	1
Drive bays 3.5" external:	1	USB 2.0 port:	1
Drive bays 5.25" external:	3	Barcode:	4260070124600
Drive bays 3.5" internal:	2	Case material:	metal
PCI slots:	7	Mark of conformity:	CE
Case fan standard/maximal:	0/3 (1x 80/92/120/140 + 1x 80 (lateral) + 1x 80/92/120 mm)	Case colour:	black
		Front panel:	black / anthracite
Case dimensions h x w x d:	425 x 180 x 450 mm	Power supply integrated:	LC420-12 V2.31 (Efficiency > 85%)
Cage dimensions h x w x d:	425 x 180 x 415 mm		
Graphic cards up to:	340 mm		
CPU cooler up to:	160 mm		
Weight (retail):	6,18 kg		

Characteristics: Incl. lateral ventilation slots on VGA and CPU level, power supply incl. 20+4 pin, 3x SATA, 1x PATA, 1x FDD, 1x 4+4 pin 12V, 1x PCI-Express 6 pin, 350W max., 120mm fan, Active PFC, efficiency > 85%, device for USB 3.0 (optional)

Note: USB 3.0 - internal mainboard connector